

GALAXY - F 153 GX VM



For illustrative purposes only

Strong points

- 1- Industrial diesel engine in genset version with certificate of origin
 - 2- Industrial brushless alternator with AVR
 - 3- Steel baseframe with retention basin, fuel tank with level sensor
 - 4- Soundproof canopy in galvanised, power coated sheet steel
 - 5- Soundproofing material made of high attenuation polyester fibre
 - 6- Internal exhaust silencer with insulated manifold
 - 7- Electrical panel mounted on board the unit with digital control device installed in metal box
 - 8- Compact for easy handling and use
 - 9- Test report, manuals and electrical drawings supplied
 - 10- World wide after sales service and technical support
- Further details on the technical data sheet**

Performance

| | |
|-------------------------------|--------------------|
| Continuous power (PRP) | 150.0 (kVA) |
| Continuous power (PRP) | 120.0 (kW) |
| Stand-by power (LTP) | 165.0 (kVA) |
| Stand-by power (LTP) | 132.0 (kW) |
| Power factor | 0.8 |

Voltage

| | |
|----------------|-------|
| Frequency (Hz) | 50 Hz |
| Voltage (V) | 400 V |

Dimensions and noise level

| | |
|---------------------|----------|
| Width | 1200 mm |
| Length | 3730 mm |
| Height | 2250 mm |
| Weight | 2980 kg |
| Sound pressure 7 m. | 65.0 dBA |

Data references

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850 gr/lt. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

Engine

| | |
|------------------|--------------|
| Engine brand | FPT IVECO |
| Engine model | N67 TE1F |
| Cylinders | 6 nr. |
| Speed | 1500 r.p.m. |
| Cubic capacity | 6.70 l |
| Air intake | Turbocharged |
| Standard voltage | 12 Vdc |
| Optional voltage | N.D. Vdc |
| Sae | N.D. |
| BMEP | 1791 kPa |
| Cooling | Water |

Engine power

| | |
|-------------------------|----------|
| Flywheel P.R.P. Power | 136.5 kW |
| Flywheel Stand-by Power | 150.0 kW |

Fuel consumption

| | |
|-----------------------------|----------|
| Fuel Cons. at 100% (L.T.P.) | 36.5 l/h |
| Fuel Cons. at 100% (P.R.P.) | 34.0 l/h |
| Fuel Cons. at 75% (P.R.P.) | 28.2 l/h |
| Fuel Cons. at 50% (P.R.P.) | 20.0 l/h |
| Fuel Cons. at 25% (P.R.P.) | N.D. l/h |

Speed regulation

| | |
|-----------------|------------|
| Type | Electronic |
| Precision class | N.D. |

Engine dimensions and liquids

| | |
|----------------------------|--------|
| Oil quantity | 12.0 l |
| Engine Antifreeze capacity | 10.5 l |
| Radiator standard | N.D. |

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.



GALAXY - F 153 GX VM

Heat from engine

| | | |
|---------------------|-------|----|
| Heat from radiator | 475.0 | kW |
| Heat from exhaust | 614.0 | kW |
| Heat from radiation | 160.0 | kW |

Exhaust data

| | | |
|---------------------|--------|--------|
| Exhaust temperature | 600 | °C |
| Cooling air flow | 228.00 | m³/min |
| Combustion air flow | 10.50 | m³/min |
| Exhaust gas flow | 782.00 | kg/h |

Emissions

| | |
|-----------|---------------|
| TA Luft | Not available |
| TA Luft/2 | Not available |
| EPA | Not available |
| Stage | Stage 3A |

Alternator

| | |
|------------------|-----------|
| Alternator brand | STAMFORD |
| Alternator model | UCI274F |
| P.R.P. Power | 160.0 kVA |
| L.T.P. Power | 175.0 kVA |

Alternator windings

| | |
|-----------------|-----------------------------|
| Connection | Series star |
| Phases | Three phases with neutral |
| Winding | 12 terminals Winding 311 |
| Terminal Number | 12 nr. |

Alternator protection

| | | |
|---------------|----|----|
| IP Protection | 23 | IP |
|---------------|----|----|

Voltage regulator

| | |
|----------------------|---------|
| Electronic regulator | SX460 |
| Precision | 1.5 ± % |

Baseframe

| | |
|----------|-------|
| Model | GV125 |
| Capacity | 850 |

Canopy & Silencer

| | |
|--------------------------|---------|
| Canopy model | GV125 |
| Silencer model | ---- |
| Silencer outlet diameter | N.D. mm |

Available control panels



Guard Touch MANUAL OR AUTOMATIC is the new revolutionary controller with touch screen, researched and developed by Visa S.p.A., which will be standard supply on our gensets. From a technical and operational viewpoint, the new device is different from its predecessors, but still maintains Visa's main characteristic: MODULARITY! Guard Touch is a versatile controller able to satisfy the myriad of requests from the end-user. From manual to automatic (AMF), up to complete synchronisation in parallel.

Optional control panels



The NEW ONIS VISA In Sync NT BB panel is based on the ComAp 'New Technology' family which is a comprehensive range of configurable Gen-set controllers suitable for managing simple, everyday or even the most complex CHP application. In addition, In Sync NT BB panel now feature one piece of software making it universally compatible with most of the leading manufacturers of electronic engines. With increased memory, more features and greater processing speed, this 'New Technology' control product have built an enviable reputation for effective system integration, simpler monitoring and more user-friendly remote supervising and servicing.

Options

Each genset model has a wide range of accessories and customised equipment choices; standard equipment and optional accessories are described in the technical data sheet. Contact our sales office for further information and details.

