

徐工徐工 助您成功  
XCMG FOR YOUR SUCCESS



# Concrete Batching Plant 混凝土搅拌站



## 工程型搅拌站

### Project Concrete Batching Plant (Modularized & Portable)

Item	Unit	HZS40KG	HZS60KG	HZS75KG
理论产能Theoretical capacity	m <sup>3</sup> /h	40	60	75
主机型号Model of main mixer		JS750	JS1000	JS1500
主机类型type of main mixer		twin shaft	twin shaft	twin shaft
搅拌功率Mixing motor power	kw	1x30	1x37	2 × 30
生产周期Working circle period	s	60	60	72
主机公称容量Rated volume of mixer	L	750	1000	1500
骨料粒径Max. aggregate diameter	mm	≤60	≤60	≤80
粉料仓容量Volume of filler silo (optional)	t	2 × 60	2x60	2 × 100
骨料斗容量Volume of aggregate bin	m <sup>3</sup>	3 × 6	3x10	3 × 10
骨料种类Species of aggregate		3	3	3
骨料供应方式feeding model of aggregate		Bucket elevator	Bucket elevator	Bucket elevator
提升斗输送能力Capacity of aggregate elevator	t/h	90	240	240
水泥螺旋输送机能力Capacity of cement screw conveyer	t/h	40	60	90
粉煤灰螺旋输送机能力Capacity of admixture screw conveyer	t/h	/	/	/
卸料高度Discharge height	m	4	4	4
额定装机容量Installed capacity	kw	74	93	148
骨料计量范围及精度Weighing range and accuracy of aggregate	kg	(500 ~ 4000) ± 2% kg	(500 ~ 4000) ± 2% kg	(500 ~ 4000) ± 2% kg
水泥计量范围及精度Weighing range and accuracy of cement	kg	(200 ~ 800) ± 1% kg	(200 ~ 800) ± 1% kg	(200 ~ 1000) ± 1% kg
粉煤灰计量范围及精度Weighing range and accuracy of fly ash	kg	/	/	/
供水计量范围及精度Weighing range and accuracy of water	kg	(100 ~ 300) ± 1% kg	(100 ~ 300) ± 1% kg	(100 ~ 350) ± 1% kg
外加剂计量范围及精度Weighing range and accuracy of additive	kg	(10 ~ 20) ± 1% kg	(10 ~ 20) ± 1% kg	(10 ~ 25) ± 1% kg

Item	Unit	HZS100KG	HZS150KG
理论产能Theoretical capacity	m <sup>3</sup> /h	100	150
主机型号Model of main mixer		JS2000A	JS3000
主机类型type of main mixer		twin shaft	twin shaft
搅拌功率Mixing motor power	kw	2 × 37	2 × 55
生产周期Working circle period	s	72	72
主机公称容量Rated volume of mixer	L	2000	3000
骨料粒径Max. aggregate diameter	mm	≤80	≤80
粉料仓容量Volume of filler silo (optional)	t	2 × 100	4 × 200
骨料斗容量Volume of aggregate bin	m <sup>3</sup>	3 × 10	4 × 25
骨料种类Species of aggregate		3	4
骨料供应方式Feeding mode of aggregate		Bucket elevator	Bucket elevator
提升斗输送能力Capacity of aggregate elevator	t/h	240	360
水泥螺旋输送机能力Capacity of cement screw conveyer	t/h	90	110
粉煤灰螺旋输送机能力Capacity of admixture screw conveyer	t/h	/	90
卸料高度Discharge height	m	4	4
额定装机容量Installed capacity	kw	160	220
骨料计量范围及精度Weighing range and accuracy of aggregate	kg	(500 ~ 5000) ± 2% kg	(1000 ~ 7500) ± 2% kg
水泥计量范围及精度Weighing range and accuracy of cement	kg	(400 ~ 1500) ± 1% kg	(400 ~ 2000) ± 1% kg
粉煤灰计量范围及精度Weighing range and accuracy of fly ash	kg	/	(200 ~ 800) ± 1% kg
供水计量范围及精度Weighing range and accuracy of water	kg	(100 ~ 400) ± 1% kg	(100 ~ 800) ± 1% kg
外加剂计量范围及精度Weighing range and accuracy of additive	kg	(10 ~ 40) ± 1% kg	(20 ~ 100) ± 1% kg

Remarks: technical data is subject to upgrade and modification of products without notification.

XUZHOU CONSTRUCTION MACHINERY GROUP CO.,LTD.  
XUZHOU XCMG SCHWING MACHINERY CO.,LTD.  
XCMG IMPORT & EXPORT CO.,LTD.

Concrete Machinery Export Department  
Tel: +86-516-87892033 87892301 83111590  
Fax: +86-516-87892035  
Email: concretemachinery@xcmg.com