

徐工徐工 助您成功
XCMG FOR YOUR SUCCESS



Concrete Batching Plant 混凝土搅拌站



商混型搅拌站

Commercial Concrete Batching Plant (Modularized & Portable)

Item	Unit	HZS90KE	HZS120KE	HZS180KE
理论产能Theoretical capacity	m ³ /h	90	120	180
主机型号Model of main mixer		JS1500	JS2000	JS3000
主机类型type of main mixer		twin shaft	twin shaft	twin shaft
搅拌功率Mixing motor power	kw	2 × 30	2 × 37	2 × 55
生产周期Working circle period	s	60	60	60
主机公称容量Rated volume of mixer	L	2400	2400	4500
骨料粒径Max. aggregate diameter	mm	≤80	≤80	≤80
粉料仓容量Volume of filler silo (optional)	t	3 × 100	3 × 150	3 × 150
骨料斗容量Volume of aggregate bin	m ³	3 × 15	4 × 15	4 × 25
骨料种类Species of aggregate		3	4	4
骨料供应方式feeding mode of aggregate		Belt conveyer	Belt conveyer	Belt conveyer
皮带机输送能力Capacity of belt conveyer	t/h	500	500	700
水泥螺旋输送机能力Capacity of cement screw conveyer	t/h	80	80	110
粉煤灰螺旋输送机能力Capacity of fly ash screw conveyer	t/h	40	40	90
卸料高度Discharge height	m	4	4	4
额定装机容量Installed capacity	kw	174	174	276
骨料计量范围及精度Weighing range and accuracy of aggregate	kg	(200~2000) ± 2%	(500~2400) ± 2%	(500~3600) ± 2%
水泥计量范围及精度Weighing range and accuracy of cement	kg	(400~1200) ± 1%	(400~1200) ± 1%	(400~1800) ± 1%
粉煤灰计量范围及精度Weighing range and accuracy of fly ash	kg	(200~600) ± 1%	(200~600) ± 1%	(200~900) ± 1%
供水计量范围及精度Weighing range and accuracy of water	kg	(100~600) ± 1%	(100~600) ± 1%	(100~800) ± 1%
外加剂计量范围及精度Weighing range and accuracy of additive	kg	(20~60) ± 1%	(20~60) ± 1%	(20~100) ± 1%

移动型搅拌站 Mobile Concrete Batching Plant (Trailer type)

Item	Unit	HZS35KY	HZS50KY	HZS75KY
理论产能Theoretical capacity	m ³ /h	35	50	75
主机型号Model of main mixer		JS750	JS1000	JS1500
主机类型type of main mixer		twin shaft	twin shaft	twin shaft
搅拌功率Mixing motor power	kw	1×30	1 × 37	2 × 30
生产周期Working circle period	s	60	60	60
主机公称容量Rated volume of mixer	L	1000	1000	1500
骨料粒径Max. aggregate diameter	mm	≤60	≤60	≤60
粉料仓容量Volume of filler silo (optional)	t	2 × 60	2 × 60	2 × 60
骨料斗容量Volume of aggregate bin	m ³	4 × 8	4 × 8	4 × 8
骨料种类Species of aggregate		4	4	4
骨料供应方式Feeding mode of aggregate		Belt conveyer	Belt conveyer	Belt conveyer
皮带机输送能力Capacity of belt conveyer	t/h	350	350	500
水泥螺旋输送机能力Capacity of cement screw conveyer	t/h	40	80	80
粉煤灰螺旋输送机能力Capacity of fly ash screw conveyer	t/h	/	/	/
卸料高度Discharge height	m	4	4	4
额定装机容量Installed capacity	kw	75	85	125
骨料计量范围及精度Weighing range and accuracy of aggregate	kg	(200~2000) ± 2%	(500~2400) ± 2%	(500~3600) ± 2%
水泥计量范围及精度Weighing range and accuracy of cement	kg	(400~1200) ± 1%	(400~1200) ± 1%	(400~1800) ± 1%
粉煤灰计量范围及精度Weighing range and accuracy of fly ash	kg	/	/	/
供水计量范围及精度Weighing range and accuracy of water	kg	(100~600) ± 1%	(100~600) ± 1%	(100~800) ± 1%
外加剂计量范围及精度Weighing range and accuracy of additive	kg	(20~60) ± 1%	(20~60) ± 1%	(20~100) ± 1%

Remarks: technical data is subject to upgrade and modification of products without notification.

UZHOU CONSTRUCTION MACHINERY GROUP CO.,LTD.
UZHOU XCMG SCHWING MACHINERY CO.,LTD.
XCMG IMPORT & EXPORT CO.,LTD.

Concrete Machinery Export Department
 Tel: +86-516-87892033 87892301 83111590
 Fax: +86-516-87892035
 Email: concretemachinery@xcmg.com